

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of)	
)	
Gary McDONALD)	Group Art Unit: Unassigned
)	
Application No.: Unassigned)	Examiner: Unassigned
)	
Filed: July 9, 2003)	Confirmation No.: Unassigned
)	
For: COMPRESSORS)	

CLAIM FOR CONVENTION PRIORITY

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

The benefit of the filing date of the following prior foreign application in the following foreign country is hereby requested, and the right of priority provided in 35 U.S.C. § 119 is hereby claimed:

United Kingdom Patent Application No. 0216346.7
Filed: July 13, 2002

In support of this claim, enclosed is a certified copy of said prior foreign application. Said prior foreign application was referred to in the oath or declaration. Acknowledgment of receipt of the certified copy is requested.

Respectfully submitted,

BURNS, DOANE, SWECKER & MATHIS, L.L.P.

Date: July 9, 2003

By: 

Platon N. Mandros
Registration No. 22,124

P.O. Box 1404
Alexandria, Virginia 22313-1404
(703) 836-6620



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.


In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed 

Dated 11 June 2003



The
Patent
Office

1/77

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road

Newport

Gwent NP9 1RH

13 JUL 2002

1. Your reference

I045.001

2. Patent application number

(The Patent Office will fill in this part)

0216346.7

1470000 5733333-1 550033

POL/7700 0.00-0216346.7

3. Full name, address and postcode of the or of each applicant (underline all surnames)

IMRA EUROPE S.A.
UK RESEARCH CENTRE
Aisin Seiki Building
The University of Sussex
Falmer
Brighton
East Sussex
BN1 9RS

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

8425050001

4. Title of the invention

Compressors

5. Name of your agent (if you have one)

SERJEANTS

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

25 The Crescent
King Street
Leicester
LE1 6RX

Patents ADP number (if you know it)

1461001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

Yes

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body.

See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 7

Claim(s) 2

Abstract 1

Drawing(s) 4 + 4 RM

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77) 1

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature Serjeants.

Date

SERJEANTS

11 July 2002

12. Name and daytime telephone number of person to contact in the United Kingdom


Darran Thacker
0116 233 2626

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.



Statement of inventorship and of right to grant of a patent

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference	I045.001
2. Patent application number (if you know it)	0216346.7
3. Full name of the or of each applicant	IMRA EUROPE S.A. UK RESEARCH CENTRE
4. Title of the invention	Compressors
5. State how the applicant(s) derived the right from the inventor(s) to be granted a patent	Assignment
6. How many, if any, additional Patents Forms 7/77 are attached to this form? (see note (c))	None
7.	<p>I/We believe that the person(s) named over the page (and on any extra copies of this form) is/are the inventor(s) of the invention which the above patent application relates to.</p> <p>Signature <i>Serjeants</i> Date</p> <p>SERJEANTS 11 July 2002</p>
8. Name and daytime telephone number of person to contact in the United Kingdom	Darran Thacker 0116 233 2626

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- d) When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- e) Once you have filled in the form you must remember to sign and date it.

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

Gary McDonald
25 Hayland Green
Harmers Hay
Hailsham
East Sussex
BN27 1SR

Patents ADP number (if you know it): 84 25068201

Patents ADP number (if you know it):

Patents ADP number (if you know it):

Reminder

Hav you signed the form?

TITLE

Compressors

DESCRIPTION

5 Technical Field

The present invention relates to compressors, and in particular to centrifugal compressors for supercharged engines.

Background Art

10 Centrifugal compressors can be used to supply air to a turbocharger unit for supercharging an engine. A conventional centrifugal compressor includes a housing defining a generally cylindrical inlet passage and a volute duct that serves as an outlet passage. The volute duct has a progressively varying sectional area.

15 An impeller is positioned between the inlet passage and the volute duct and includes a number of curved blades capable of imparting kinetic energy to the air when the impeller is rotated. Air is drawn through the inlet passage by the impeller and then supplied to the volute duct. The kinetic energy stored within the air is converted into static pressure as it expands under controlled conditions within the volute duct. The
20 impeller can also be surrounded by a diffuser section which helps to direct the air leaving the impeller into the duct.

Conventional centrifugal compressors have a high efficiency area of operation but are less efficient at low mass flow rates. It is well known that the efficiency of
25 conventional centrifugal compressors can be increased for low mass flow rates if the flow angle of the air is altered before it reaches the impeller. More particularly, the efficiency can be increased if the air is given a rotary component of movement in the same direction as the rotation direction of the impeller.

30 United States Patent No. 6,039,534 describes one way of altering the flow angle of the inlet air by placing a plurality of inlet guide vanes in the inlet passage upstream of the impeller. The inlet guide vanes are pivotally mounted within a guide vane housing

and can be selectively pivoted in unison to alter the flow angle of the air in response to different mass flow rates. This enables the centrifugal compressor to be operated at high efficiency over a wide range of mass flow rates.

- 5 There are two main problems with pivotally mounted inlet guide vanes. The first is the complex structure needed to mount the inlet guide vanes and control the pivoting movement of all the guide vanes in synchronisation. The second is the reduction in the sectional area of the inlet passage. The inlet guide vanes are closely spaced and therefore reduce the amount of air that can be drawn through the inlet passage by the
10 impeller.

The present invention seeks to address these problems by providing a centrifugal compressor which has a simple structure with minimal reduction in the sectional area of the inlet passage.

- 15 Although the present invention has been described with reference to centrifugal compressors, the same principle can be applied to axial flow compressors as used in industrial gas turbine engines and jet engines.

20 Summary of the Invention

- The present invention provides a compressor comprising a housing defining a fluid inlet passage and a fluid outlet passage, a rotary impeller located within the housing between the fluid inlet passage and the fluid outlet passage, and a plurality of inlet guide vanes in the inlet passage for imparting a rotary component of movement to
25 fluid passing through the fluid inlet passage for increasing efficiency at low mass flow rates, characterised in that a sleeve is mounted axially in the fluid inlet passage and divides the fluid inlet passage into a radially outer portion and a radially inner portion, the inlet guide vanes are located in the radially outer portion of the fluid inlet passage, and a fluid flow cut-off valve is provided in the radially inner portion of the fluid inlet
30 passage for selectively preventing fluid flow therethrough and diverting all of the fluid through the radially outer portion of the fluid inlet passage at low mass flow rates.

The fluid flow cut-off valve is movable between a closed position where fluid can only flow through the radially outer portion of the fluid inlet passage and an open position where fluid can flow through the radially inner and outer portions of the fluid inlet passage. Because the inlet guide vanes are located in the radially outer portion of the fluid inlet passage it means that the radially inner portion of the fluid inlet passage has the least resistance to fluid flow. It will therefore be readily appreciated that when the fluid flow cut-off valve is open the majority of the fluid will pass through the radially inner portion of the fluid inlet passage.

10

At low mass flow rates the fluid flow cut-off valve is moved to the closed position such that the fluid is made to flow through the radially outer portion of the fluid inlet passage. The inlet guide vanes impart a rotary component of movement to the fluid in the same direction as the rotation direction of the impeller. This increases the efficiency of the compressor at low mass flow rates. At high mass flow rate, the compressor operates more efficiently if the fluid has no rotary component of movement. The fluid flow cut-off valve is therefore moved to the open position such that most of the fluid is made to flow straight through the radially inner portion of the fluid inlet passage.

20

The centrifugal compressor according to the present invention can therefore be operated at high efficiency over a wide range of mass flow rates.

The inlet guide vanes preferably have a fixed vane angle so that the compressor has a simple construction. However, it will be readily appreciated that the inlet guide vanes can be pivotally mounted such that they have a variable vane angle. The inlet guide vanes preferably have a vane angle of up to 70°.

25

The fluid flow cut-off valve is preferably located at an upstream portion of the sleeve but it can be mounted at either end of the sleeve or at any intermediate position. The fluid flow cut-off valve is preferably mounted by means of a pivotal mounting such as a rod that extends across the housing.

30

The inlet guide vanes are preferably fixed to the outer surface of the sleeve and preferably take the form of curved blades. The inlet guide vanes and the sleeve can be integrally formed or the inlet guide vanes can be welded or bonded to the sleeve.

5

The sleeve and the inlet guide vanes are preferably maintained in position by frictional contact with the housing as well as by the pivotal mounting for the fluid flow cut-off valve.

10

The sleeve preferably has a greater axial length than the inlet guide vanes but it can have the same axial length. The inlet guide vanes are preferably located at a downstream portion of the sleeve but they can be mounted at either end of the sleeve or at any intermediate position. The fluid flow cut off valve is preferably located upstream from the inlet guide vanes.

15

The sleeve preferably has an aerodynamic profile in the axial direction. This helps to ensure that the fluid flow past the sleeve is turbulence free.

20

The sleeve is preferably axially mounted such that the sectional area of the radially outer portion of the fluid inlet passage is the same as the sectional area of the radially inner portion of the fluid inlet passage. The sectional area occupied by the inlet guide vanes can be taken into consideration when calculating the distance between the outer surface of the sleeve and the housing.

25

The sleeve and the part of the housing that surrounds the sleeve are preferably substantially cylindrical. The housing also preferably tapers from the substantially cylindrical part towards the impeller such that the diameter of the fluid inlet passage adjacent the impeller is the same as that of the sleeve. The axial distance from the sleeve to the impeller is selected for optimum efficiency.

30

The compressor may also include a diffuser surrounding the impeller.

Drawings

Figure 1 is a sectional view of a centrifugal compressor according to the present invention;

Figure 2 is a cross-sectional view taken along line A-A of Figure 1;

5 Figure 3 is a perspective view showing the sleeve and inlet guide vanes of Figure 1;

Figure 4 is a graph showing the efficiency of the centrifugal compressor of Figure 1 for different flow angles at the same operating speed; and

Figure 5 is a graph showing the pressure ration of the centrifugal compressor of Figure 1 for different flow angles at the same operating speed.

10

Figure 1 shows a centrifugal compressor. The compressor has a housing 1 which defines an inlet passage 2 and a volute duct (not shown). A cylindrical sleeve 3 is mounted axially within the inlet passage 2 and divides the inlet passage into a radially outer portion 4 and a radially inner portion 5.

15

The housing 1 has a substantially cylindrical portion that surrounds the sleeve 2. The inner diameter of the cylindrical portion of the housing is approximately $\sqrt{2}$ times the inner diameter of the sleeve 3 such that the sectional flow area through the radially outer portion 4 is the same as that through the radially inner portion 5.

20

A rotary impeller 6 is located within the housing 1 between the inlet passage 2 and the volute duct (not shown). As the impeller 6 rotates, air is drawn through the inlet passage 2 and supplied to the volute duct (not shown).

25

The housing 1 also has a tapered portion extending from the cylindrical portion towards the impeller 6 and ending in a substantially cylindrical collar 7. The inner diameter of the collar 7 is the same as the inner diameter of the sleeve 3, so that at maximum mass flow rates the intake air can pass through the radially inner portion 5 and through the cylindrical collar 7 without compression.

30

With reference to Figure 3, a number of curved blades 8 are integrally formed on the outer surface of the sleeve 3. The blades 8 are located in the radially outer portion 4

of the inlet passage 2 and impart a rotary component of movement in the same direction as the rotation direction of the impeller 6 to any air passing through the radially outer portion 4 (represented by the solid block arrows in Figure 1). The step of imparting a rotary component of movement to the air passing through the inlet passage 2 is commonly known as "pre-swirl".

The curvature of the blades 8 is selected to impart a particular swirl angle to the air flowing through the radially outer portion 4. Figure 4 shows how the efficiency of the compressor varies with the mass flow of air passing through the inlet passage 2 and the swirl angle. It is clear from Figure 4 that 0° (no swirl angle) is most efficient at high mass flow rates but is less efficient for mass flow rates below 60 g/s. For mass flow rates below this figure it is more efficient for the curved blades 8 to impart a swirl angle of 50° or 70° to the air. The operational speed of the impeller 6 is fixed.

A flap valve 9 is located in the radially inner portion 5 of the inlet passage 2 as shown in Figures 1 and 2. The flap valve 9 is pivotally mounted on a shaft 10 and can be pivoted between a closed position (represented by the block line in Figure 1) and an open position (represented by the dotted line in Figure 1). The shaft 10 is positioned such that it does not interfere with the curved blades 8. Although both ends of the shaft 10 are shown to be inserted into the housing 1, it is possible that only one end is inserted into the housing so as to support the flap valve 9. When the compressor is operating at high mass flow rate, for example above 60 g/s, then the flap valve 9 is pivoted to the open position and the air is drawn through the radially inner portion 5 (as represented by the dotted arrow in Figure 1) and the radially outer portion 4. It will be readily appreciated that only a small amount of air will be drawn through the radially outer portion 4 of the inlet passage 2 because of the increased resistance to air flow compared to the radially inner portion 5. This means that the majority of the air supplied to the impeller 6 at high mass flow rates will not be swirled.

When the compressor is operating at low mass flow rate, for example below 60 g/s, then the flap valve 9 is pivoted to the closed position and the air is drawn only

through the radially outer portion 4 of the inlet passage 2 where the curved blades 8 impart a particular swirl angle in the rotation direction of the impeller 6.

5 In this way the compressor is able to maximise its efficiency for different mass flow rates.

Figure 5 shows how the pressure ratio of the compressor varies with the mass flow rate of air passing through the inlet passage 2 and the swirl angle. It is clear from Figure 5 that a 70° swirl angle is most efficient at reducing the surge area.

10

CLAIMS

1. A compressor comprising:
 - a housing defining a fluid inlet passage and a fluid outlet passage;
 - 5 a rotary impeller located within the housing between the fluid inlet passage and the fluid outlet passage;
 - a plurality of inlet guide vanes in the inlet passage for imparting a rotary component of movement to fluid passing through the fluid inlet passage for increasing efficiency at low mass flow rates;
 - 10 characterised in that:
 - a sleeve is mounted axially in the fluid inlet passage and divides the fluid inlet passage into a radially outer portion and a radially inner portion;
 - the inlet guide vanes are located in the radially outer portion of the fluid inlet passage; and
 - 15 a fluid flow cut-off valve is provided in the radially inner portion of the fluid inlet passage for selectively preventing fluid flow therethrough and diverting all of the fluid through the radially outer portion of the fluid inlet passage at low mass flow rates.
- 20 2. A compressor according to claim 1, wherein the inlet guide vanes have a fixed vane angle.
3. A compressor according to claim 2, wherein the inlet guide vanes have a vane angle of up to 70°.
- 25 4. A compressor according to claim 2, wherein the fluid flow cut-off valve is located in the sleeve by means of a pivotal mounting.
5. A compressor according to any preceding claim, wherein the inlet guide vanes
30 are fixed to the outer surface of the sleeve.

6. A compressor according to claim 4 or claim 5, wherein the sleeve and the inlet guide vanes are maintained in position by frictional contact with the housing and the pivotal mounting for the fluid flow cut off valve.
- 5 7. A compressor according to any preceding claim, wherein the sleeve has a greater axial length than that of the inlet guide vanes.
8. A compressor according to any preceding claim, wherein the inlet guide vanes are located at a downstream portion of the sleeve.
- 10 9. A compressor according to any preceding claim, wherein the fluid flow cut-off valve is located at an upstream portion of the sleeve.
- 15 10. A compressor according to any preceding claim, wherein the diameter of the fluid inlet passage adjacent the impeller is the same as the diameter of the sleeve.
11. A compressor according to any preceding claim, further comprising a diffuser surrounding the impeller.
- 20 12. A compressor substantially as herein described with reference to the drawings.

TITLE

Compressors

(Figure 1)


5

ABSTRACT

The present invention provides a compressor comprising a housing 1 defining an air inlet passage 2 and a volute duct. A rotary impeller 6 is located within the housing 1 between the inlet passage 2 and the volute duct. A sleeve 3 is mounted axially in the inlet passage 2 and divides the inlet passage into a radially outer portion 4 and a radially inner portion 5. A plurality of inlet guide vanes 8 are positioned in the radially outer portion 4 and impart a rotary component of movement pre-swirl) to air passing through the inlet passage 2. A fluid cut-off valve 9 is positioned in the radially inner portion 5 and for selectively preventing fluid flow therethrough and diverting all of the air through the radially outer portion 4 of the inlet passage 2 at low mass flow rates.

10

15







Figure 1



A - A

Figure 2




Figure 3




Figure 4




Figure 5

BURNS, DOANE, SWECKER & MATHIS, L.L.P.
APPLN. FILING DATE: July 9, 2003
ATTORNEY DOCKET NO.: 000411-001
TITLE: COMPRESSORS
INVENTOR: Gary McDONALD